


標準断面図

S=1:50



道路用L型擁壁 数量表

H (mm)	タイプ	B (mm)	T1 (mm)	a (mm)	b (mm)	製品重量 (kg)	基礎工数量(延長10m当り)			
							コンクリート (m ³)	均し型枠 (m ²)	基礎材 (m ²)	敷モザル (m ²)
750	A	600	100	200	100	499	0.800	2.00	10.00	0.180
	B	750				548	0.950		11.50	0.225
	C	900				598	1.100		13.00	0.270
1000	A	800	100	200	100	684	1.000	2.00	12.00	0.240
	B	1000				750	1.200		14.00	0.300
	C	1200				816	1.400		16.00	0.360
1250	A	1000	100	200	100	957	1.200	2.00	14.00	0.300
	B	1250				1047	1.450		16.50	0.375
	C	1500				1137	1.700		19.00	0.450
1500	A	1050	100	200	100	1111	1.250	2.00	14.50	0.315
	B	1200				1167	1.400		16.00	0.360
	C	1350				1224	1.550		17.50	0.405
	D	1500				1280	1.700		19.00	0.450
1750	A	1225	120	200	100	1498	1.425	2.00	16.25	0.368
	B	1400				1573	1.600		18.00	0.420
	C	1575				1647	1.775		19.75	0.473
	D	1750				1722	1.950		21.50	0.525
2000	A	1400	120	200	100	1785	1.600	2.00	18.00	0.420
	B	1600				1872	1.800		20.00	0.480
	C	1800				1958	2.000		22.00	0.540
	D	2000				2045	2.200		24.00	0.600
2250	A	1575	120	200	100	2144	1.775	2.00	19.75	0.473
	B	1800				2253	2.000		22.00	0.540
	C	2025				2362	2.250		24.25	0.608
	D	2250				2470	2.450		26.50	0.675
2500	A	1750	120	200	100	2481	1.950	2.00	21.50	0.525
	B	2000				2604	2.200		24.00	0.600
	C	2250				2727	2.450		26.50	0.675
	D	2500				2850	2.700		29.00	0.750
2750	A	1925	120	200	100	2966	2.125	2.00	23.25	0.578
	B	2200				3127	2.400		26.00	0.660
	C	2475				3288	2.675		28.75	0.743
	D	2750				3448	2.950		31.50	0.825
3000	A	2100	120	200	100	3359	2.300	2.00	25.00	0.630
	B	2400				3537	2.600		28.00	0.720
	C	2700				3715	2.900		31.00	0.810
	D	3000				3893	3.200		34.00	0.900

注) 基礎工の寸法及び数量は、いずれも参考値です。
注) 製品重量は、製品長 L=2.0m (標準品) の重量です。